

Titanium® UDL25 is a highly engineered, mechanically attached, coated woven synthetic roofing underlayment designed for sloped roofs. UDL25 represents the future in felt replacement technology, and used in conjunction with Titanium PSU30 self-adhered underlayment, offers the sloped roofing industry a truly revolutionary system of safety, security and simplicity.

UDL25's advanced polymers combine to deliver a unique gray synthetic roofing underlayment that can be used under all types of primary roofing materials to replace #30 felt. Gray technology provides for a cooler working surface during installations and up to a 6 month UV exposure. Unlike smooth surfaced underlayments, UDL25 possesses a revolutionary patented slip resistant Sure-Foot® nodular walking surface technology that allows for easier steep slope walkability, even in wet conditions.

Gain an edge in productivity and profits; UDL25's light weight, 48" width and 250 ft run length allows for fewer laps, cuts and easier roll handling compared to felt. This means you can do more jobs in less time, use less labor, and inventory fewer rolls.

UDL25 is 100% synthetic, therefore totally unaffected by water, which means it is 100% inert to mold, lays flat and will not wrinkle. Stay on track, take on more jobs and sleep assured that your UDL25 projects will remain intact and dried-in. Unlike felts, UDL25 does not dry out, leach oils in the heat, nor does it become stiff, difficult to roll or crack in the cold.


UDL25 is 14 times stronger than #30 felt, gone are the days of blow-offs and call backs! Exceptional tear strength and up to 6 months exposure time allows your job to stay on track through all kinds of wind and weather. Less material damage and waste during installation and fewer post-install repairs result in significant savings in time and money. UDL25 will continue to protect your high cost, long life rated, primary roofing long after oil saturated felt products have turned to dust!



Turn your next roofing job into a . . .

**MASSIMO
BILLBO**

- Up to 6 months UV exposure rating
- Meets and exceeds ASTM D226 Types I & II
- ICC ES Approved
- Class A Fire ASTM E108
- CAN/CSA A220.1
- Meets Class 4 Hail Rating
- Florida Building Code Approved
- Texas Department of Insurance
- 11 times lighter and 14 times stronger than #30 felt
- Contributes to LEED® points, 100% Recyclable
- All temperature performance -40°F to 240°F
- Synthetic construction inert to mold growth
- Cool gray surface, doesn't expand or contract
- Dual logo custom printing available



TITANIUM UDL25 ROLL SPECS

LENGTH PER ROLL:	250' / 76.2 m
WIDTH PER ROLL:	48" / 122 cm
WEIGHT PER ROLL:	25 lbs / 11.5 kg
ROLL SIZE:	10 sq / 93 m ²
ROLLS PER PALLET:	56
PALLET WEIGHT:	1,450 lbs / 658 kg

TITANIUM UDL25 TECHNICAL DATA

TEST & STANDARD*	TITANIUM UDL25 TYPICAL VALUE	ASTM #30 FELT TYPICAL VALUE
Class A Fire ASTM E108	Pass	N/A
Nail Sealability ASTM D1970	Pass	N/A
Permeability ASTM E96	.06 perms	1.75 perms
Water Transmission ASTM D4869	Pass	Pass
Tear Strength ASTM D4533	MD 31 lbs (14 kg) CD 27 lbs (12.5 kg)	MD 4 lbs (1.8 kg) CD 2 lbs (0.9 kg)
Tensile Strength ASTM D751	MD 135 lbs (61 kg) CD 100 lbs (45.5 kg)	MD 70 lbs (32 kg) CD 38 lbs (17 kg)
Burst Strength ASTM D751	220 psi (1517 kPa)	62 psi (430 kPa)
Elongation ASTM D751	MD 17% CD 20%	MD 2% CD 2%
Weight per Square ASTM D5261	2.4 lbs (1.1 kgs)	27.5 lbs (12.5 kgs)
Minimum Thickness ASTM D1777	15 mils (0.38 mm)	60 mils (1.5 mm)

InterWrap® Roofing Products Division

Charleston, SC • Vancouver, BC • Mission, BC • Montréal, QC
www.InterWrap.com/titanium
 Toll Free: 888 713 7663 | Tel: 778 945 2888
 E-mail: info@interwrap.com

*Titanium brand products are manufactured in accordance with national standards which allow for non-critical variances in weights and measurements. Test data is based on an average taken over